

MULTI

Unità Interne *AEOLOS*



Telecomando

Modello	Unità interna		SFM-09ALSI-AU1	SFM-12ALSI-AU1	SFM-18ALSI-AU1
Capacità	Raffrescamento	Btu/h	9000(4780-11260)	12285(5800-12625)	17747(8530-19790)
		kW	2.58(1.40-3.30)	3.50(1.70-3.70)	5.27(2.50-5.80)
	Riscaldamento	Btu/h	9215(4095-10240)	12625(5120-12625)	18085(7680-19790)
		kW	2.70(1.20-3.00)	3.50(1.50-3.70)	5.37(2.25-5.80)
Dati elettrici	Alimentazione	V~,Hz,Ph	220~240,50,1	220~240,50,1	220~240,50,1
	Assorbimento in raffrescamento	W	40(12~68)	40(12~68)	63(16~88)
	Assorbimento in riscaldamento	W	40(12~68)	40(12~68)	63(16~88)
Motore Ventola	Potenza	W	12	12	30
	Velocità (Alta/Media/Bassa)	r/min	1150	1150	1330
Performance	Portata d'aria	m ³ /h	600	600	850
	Pressione sonora	dB(A)	40/38/34	42/40/37	45/42/37
	Potenza sonora	dB(A)	54	52	55
Dimensioni	Dimensioni nette (L*P*H)	mm	792x201x292	792x201x292	940x224x316
	Dimensioni imballo (L*P*H)	mm	888x290x370	888x290x370	1010x310x385
Peso	Netto	kg	8	8,5	12
	Lordo	kg	10	10,5	14
Refrigerante			R32	R32	R32
Diametro tubi	Lato liquido	mm(inch)	6.35(1/4)	6.35(1/4)	6.35(1/4)
	Lato gas	mm(inch)	9.52(3/8)	9.52(3/8)	12.7(1/2)
	Drenaggio	mm	16,5	16,5	16,5

Note: SENDO si riserva il diritto di cambiare i dati tecnici in tabella senza preavviso.